

# LEICA DISTO D910



## SPESIFIKASI

- Measuring accuracy (favorable conditions) 1.0mm /  $\pm$  0.04 in\*
- Measuring accuracy (unfavorable conditions) 2.0mm /  $\pm$  0.08 in\*\*
- Range (favorable conditions) 0.05m - 300m / 0.16 ft - 984 ft
- Range (unfavorable conditions) 0.05m - 150m / 0.16 ft - 492 ft
- Smart Base vertical range  $-40^{\circ}$  to  $80^{\circ}$
- Smart Base vertical sensor tolerance up to  $\pm$  0.1°
- Smart Base horizontal range  $360^{\circ}$
- Smart Base horizontal tolerance up to  $\pm$  0.1°
- Tolerance P2P function at distances (combination of sensors and distance measuring) approx.  $\pm$  2 mm / 2 m  $\pm$  5 mm / 5 m  $\pm$  10 mm / 10 m
- Measuring units 0.000 m, 0.0000 m, 0.00 m, 0.00 ft, 0'00" 1/32, 0.00 in, 0 in 1/32
- X-Range Technology Yes
- Pointfinder with 4x zoom Yes
- Overview camera Yes
- File format .jpg / .dxf
- Memory Last 50 displays



@plazagps



@plazagps store



@plazagps01

**PLAZA GPS**  
GPS, Telescope & Surveying

Mall WTC Matahari Serpong LT.2 Blok S.20

Tlp : 021-53153871

Watsapp : 081298737575

Web : www.plazagps.com